Yuasa Ficha Técnica

Yuasa ENL100-12FT Industrial VRLA Battery



Especificaciones	
Voltaje nominal (V)	12
10-hr de capacidad 1.8V/celdaa 20°C (Ah)	100
Dimensiones	
Largo (mm)	558 (±3)
Ancho (mm)	125 (±2)
Alto (mm)	233 (±2)
Peso (Kg)	41
Tipo de terminal	
M= Masculino, F=Femenino	M6 (M)
Tuerca (Nm)	6 (±0.5)
Rango de temperatura de funcionamiento	
Almacenamiento (en carga completa)	-20°C to +50°C
Carga	-15°C to +50°C
Descarga	-20°C to +60°C
Almacenamiento	
Perdida de capacidad por mes a 20º C (% aprox.)	3
Material de la caja	
Standar	ABS (UL94:V0)
Voltaje de carga	
Carga flotante a 20°C (V)/Block	13.56 (±1%)
Carga flotante a 20°C (V)/Cell	2.26 (±1%)
Voltaje de carga en flotación factor de corrección de la termperatura desde estándar a 20º C (mV)	-3
Voltaje a carga ciclica a 20°C (V)/Block	14.4 (±2%)
Voltaje a carga ciclica 20°C (V)/Cell	2.40 (±2%)
Carga de voltaje en ciclos factor de correcion de temperatura desde 20º (mV)	-4
Corriente de carga	
Limite de carga de corriente en flotación (A)	No limit
Carga ciclica. Limite	25
Máxima corriente de carga	
1 segundo (A)	500
1 minuto (A)	200
Corriente de corto circuito y resitencia interna	
Resistencia interna - en función del EN IEC 60896-21 (mΩ)	7.42
Corriente de corto circuito - en función del EN IEC 60896-21 (A)	1905
Impedancia	
Medida a 1 kHz (mΩ)	7.5
Diseño de vida y certificados	
Clasificado Eurobat: Extra larga vida	12+ years
Diseño de vida Yuasa a 20ºC (años)	15 years

Certificados de otras empresas
ISO9001 - Sistemas de gestión de Calidad
ISO14001 - Sistemas de gestión ambiental
ISO45001 OHSAS Management Systems
UNDERWRITERS LABORATORIES Inc.

Cert. No.: FM 10626

Cert. No.: EMS 55229

Seguridad

Instalación
Puede ser instalado y trabajar en cualquier orientación excepto de manera invertida de forma permanente.

Asas
Las baterías no deben estar sujetas por sus asas (si existen).

Válvulas ventiladas
Cada celda está equipada con una válvula de liberación de presión baja para permitir que los gases escapen y luego vuelven a sellar.

Liberación de gas
Baterías VRLA liberan gas hidrógeno que puede formar mezclas explosivas en el aire. No coloque dentro de un recipiente hermético.

Reciclaje
Baterías de YUASA VRLA deben reciclar al final de la vida , de acuerdo con las leyes y regulaciones locales y nacionales.

Fecha de emision: 29/03/2024 - E&EO

Yuasa Technical Data Sheet

Yuasa ENL100-12FT Industrial VRLA Battery



Specifications	
Nominal voltage (V)	12
10-hr rate Capacity to 1.8V/Cell at 20°C (Ah)	100
Dimensions	
Length (mm)	558 (±3)
Width (mm)	125 (±2)
Height (mm)	233 (±2)
Mass (kg)	41
Terminal Type	
Threaded terminal - (M=Male or F=Female)	M6 (M)
Torque (Nm)	6 (±0.5)
Operating Temperature Range	
Storage (in fully charged condition)	-20°C to +50°C
Charge	-15°C to +50°C
Discharge	-20°C to +60°C
Storage	
Capacity loss per month at 20°C (% approx.)	3
Case Material	
Standard	ABS (UL94:V0)
Charge Voltage	
Float charge voltage at 20°C (V)/Block	13.56 (±1%)
Float charge voltage at 20°C (V)/Cell	2.26 (±1%)
Float Chg voltage tmp correction factor from std 20°C (mV)	-3
Cyclic (or Boost) charge Voltage at 20°C (V)/Block	14.4 (±2%)
Cyclic (or Boost) charge Voltage at 20°C (V)/Cell	2.40 (±2%)
Cyclic Chg voltage tmp correction factor from std 20°C (mV)	-4
Charge Current	
Float charge current limit (A)	No limit
Cyclic (or Boost) charge current limit (A)	25
Maximum Discharge Current	
1 second (A)	500
1 minute (A)	200
Short-Circuit Current & Internal Resistance	
Internal resistance - according to EN IEC 60896-21 (mΩ)	7.42
Short-Circuit current - according to EN IEC 60896-21 (A)	1905
Impedance	
Measured at 1 kHz (mΩ)	7.5
Design Life & Approvals	
EUROBAT Classification: Very Long Life	12+ years
Yuasa design life at 20°C (yrs)	15 years

3rd Party Certifications
ISO9001 - Quality Management Systems
ISO14001 - Environmental Management Systems
ISO45001 OHSAS Management Systems
UNDERWRITERS LABORATORIES Inc.

Safety

Installation
Can be installed and operated in any orientation except permanently inverted.

Handles
Batteries must not be suspended by their handles (where fitted).

Vent valves
Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

Gas release
VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

Recycling
YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.

Data Sheet generated on 29/03/2024 – E&OE