Yuasa Ficha Técnica

* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

Yuasa YBX3053 - YBX3000 SMF

Rendimiento

Tensión	12V
Capacidad (20 horas)	45Ah
Capacidad Arranque Amperios (EN1)	400A



Dimensiones

Largo	238mm
Ancho	129mm
Alto	225mm

Peso

Peso con Acido	12.4kg

Caracteristicas


Tipo de Caja	JIS B24
Fijación	N
Indicador de Carga	✔
Asas	✔
Respiradero	✔
Sellada	SMF doble tapa

Tecnología


Regulador gases	✔
Tecnología	Ca/Ca
Separadores	PE
Prueba de vuelco de VDA	✔
Carga recomendada	3A
Performance Marking	W3-C2-V2-E1

Tipo de terminal

T1/T3
Standard DIN Post



Esquema



Fijación



Fecha de emision: 29/03/2024 - E&EO

Yuasa Technical Data Sheet

* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

Yuasa YBX3053 - YBX3000 SMF Batteries

Performance

Voltage	12V
Capacity (20-hour)	45Ah
Cold Cranking Amps (EN1)	400A



Dimensions

Length	238mm
Width	129mm
Height	225mm

Weights & Measures

Mean Weight with Acid	12.4kg

Container Features


Case Type	JIS B24
Hold Down	N
State of Charge Indicator	✔
Handles	✔
End Venting	✔
Lid Type	SMF Double Lid

Technology


Flame Arrestor	✔
Technology	Ca/Ca
Separator	PE
VDA Roll Over Test	✔
Recommended Charge Rate	3A
Performance Marking	W3-C2-V2-E1

Terminal Type

T1/T3
Standard DIN Post



Cell Assembly Layout



Battery Hold-down



Data Sheet generated on 29/03/2024 – E&OE